



SHERWIN-WILLIAMS  
210-C BLANDING BLVD  
ORANGE PARK, FL 32073 3339  
(904) 272-7777

03/14/2018  
Quote #: 4105536

WATERMILL MASTER ASSOC. INC  
9351 ARGYLE FOREST BLVD  
JACKSONVILLE FL 322448417

Re: Price Quote for watermill homeowner's paint pricing

Dear Chris,

Here is your special pricing on Superpaint interior and exterior paints. Of course you will receive a discount on other paints as well. This is close to 50% off of list price for Superpaint. Thank you very much!

Should you require assistance or have any questions or concerns, please contact me at (904) 509-5072 or e-mail me at [glen.g.greathouse@sherwin.com](mailto:glen.g.greathouse@sherwin.com).

Sincerely,

Glen Greathouse  
Sherwin-Williams  
Sales Representative



**SHERWIN  
WILLIAMS.**

## PRICE QUOTATION

Account #: 2508-2749-0

03/14/2018  
Quote #: 4105536

WATERMILL MASTER ASSOC. INC  
9351 ARGYLE FOREST BLVD  
JACKSONVILLE, FL 322448417  
(904) 729-5848

<b>Project:</b>	WATERMILL HOMEOWNER'S PAINT PRICING
<b>Start Date:</b>	03/14/2018
<b>Completion Date:</b>	06/13/2018
<b>Purchase Type:</b>	Single Purchase

### We are pleased to quote you as follows:

SALES NUMBER	SIZE	PRODUCT/REX NUMBER	DESCRIPTION	QTY	PRICE
6404-13720	GALLON	A80W01151	SuperPaint® Exterior Latex Flat Extra White	1	\$29.18
6404-13761	GALLON	A89W01151	SuperPaint® Exterior Latex Satin Extra White	1	\$30.19
6500-47574	GALLON	A84W01151	SuperPaint® Latex Gloss House & Trim Paint Extra White	1	\$31.19
6500-41254	GALLON	A86W00151	SuperPaint® Interior Latex Flat Extra White	1	\$29.18
6500-41361	GALLON	A87W00151	SuperPaint® Interior Latex Satin Extra White	1	\$30.19
6404-12730	GALLON	A88W00151	SuperPaint® Interior Latex Semi-Gloss Extra White	2	\$31.19

We thank you for your consideration of Sherwin-Williams products and look forward to supplying these products to you.

Note: All prices are per gallon/unit.

### TERMS OF THE SALE

Quotation Expires: 06/13/2018  
F.O.B. Location:  
Freight Terms:  
Terms: As Agreed

By: Daniel Greathouse

Store Address: 210-C BLANDING BLVD  
City: ORANGE PARK State: FL Zip: 32073 3339  
Store Number: 2178  
Phone: (904) 272-7777  
Territory #: 4097

NOTICE: Please take notice that the quotation set forth above is not a contract and is subject to and conditioned upon approval by SHERWIN-WILLIAMS. In the event such approval is not obtained, you will be provided with a revised quotation and the quotation set forth above shall be null, void and of no force or effect. The pricing and recommendations detailed in this proposal represent confidential information provided by SHERWIN-WILLIAMS. We request that it not to be copied or shared with others outside your firm.

# Data Pages



**SHERWIN  
WILLIAMS.**



# SUPERPAINT®

## Exterior Latex Flat

- A80W00116 Super White
- A80W01151 Extra White
- A80W00153 Deep Base
- A80T01154 Ultradeep Base
- A80Y00156 Light Yellow

As of 03/08/2018, Complies with:			
OTC	Yes	LEED® 09 NC CI	N/A
OTC Phase II	Yes	LEED® 09 CS	N/A
SCAQMD	Yes	LEED® v4 Emissions	N/A
CARB	Yes	LEED® v4 VOC	Yes
CARB SCM2007	Yes		
Canada	Yes	MPI	Yes

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>															
<p><b>SuperPaint Exterior Latex Flat</b>, with resistance to early dirt pick up, provides outstanding performance on properly prepared aluminum and vinyl siding, wood, hardboard, masonry, cement, brick, block, stucco, and metal down to a surface and air temperature of 35°F.</p> <p><b>VinylSafe™</b> paint colors allow you the freedom to choose from 100 color options, including a limited selection of darker colors formulated to resist warping or buckling when applied to a sound, stable vinyl substrate.</p> <p><b>Color:</b> Most colors To optimize hide and color development, always use the recommended P-Shade primer</p> <p><b>Coverage:</b> 350 - 400 sq ft/gal @ 4 mils wet; 1.4 mils dry</p> <p><b>Drying Time, @ 50% RH:</b> @ 35-45°F @ 45°F+</p> <p>Touch: 2 hour 2 hours Recoat: 24-48 hours 4 hours</p> <p>Drying and recoat times are temperature, humidity, and film thickness dependent</p> <p><b>Finish:</b> 0-5 units @ 85°</p> <p><b>Tinting with CCE:</b></p> <table border="1"> <thead> <tr> <th>Base</th> <th>oz/gal</th> <th>Strength</th> </tr> </thead> <tbody> <tr> <td>Extra White</td> <td>0-6</td> <td>SherColor</td> </tr> <tr> <td>Deep Base</td> <td>4-12</td> <td>SherColor</td> </tr> <tr> <td>Ultradeep Base</td> <td>10-12</td> <td>SherColor</td> </tr> <tr> <td>Light Yellow</td> <td>2-12</td> <td>SherColor</td> </tr> </tbody> </table> <p><b>Extra White A80W01151</b> (may vary by base)</p> <p><b>VOC (less exempt solvents):</b> &lt;50 g/L; &lt;0.42 lb/gal As per 40 CFR 59.406 and SOR/2009-264, s.12</p> <p><b>Volume Solids:</b> 36 ± 2%</p> <p><b>Weight Solids:</b> 53 ± 2%</p> <p><b>Weight per Gallon:</b> 11.38 lb</p> <p><b>Flash Point:</b> N/A</p> <p><b>Vehicle Type:</b> 100% Acrylic</p> <p><b>WVP Perms (US)</b> 33.14 grains/(hr ft<sup>2</sup> in Hg)</p> <p><b>Mildew Resistant</b> This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p>	Base	oz/gal	Strength	Extra White	0-6	SherColor	Deep Base	4-12	SherColor	Ultradeep Base	10-12	SherColor	Light Yellow	2-12	SherColor	<p>SuperPaint Exterior Latex Flat can be self-priming when used directly over existing coatings, or bare drywall, plaster and masonry (with a cured pH of less than 9). The first coat acts like a coat of primer and the second coat provides the final appearance and performance. Please note that some specific surfaces require specialized treatment.</p> <p><b>Aluminum &amp; Aluminum Siding<sup>1</sup>, Galvanized Steel<sup>1</sup>, Vinyl Siding</b> 2 cts. SuperPaint Exterior Latex</p> <p><b>Concrete Block, CMU, Split Face Block</b> 1 ct. Loxon Block Surfacer 2 cts. SuperPaint Exterior Latex</p> <p><b>Brick</b> 1 ct. Loxon Conditioner<sup>2</sup> 2 cts. SuperPaint Exterior Latex</p> <p><b>Cement Composition Siding/Panels</b> 1 ct. Loxon Concrete &amp; Masonry Primer<sup>2</sup> or Loxon Conditioner<sup>2</sup> 2 cts. SuperPaint Exterior Latex</p> <p><b>Stucco, Cement, Concrete</b> 1 ct. Loxon Concrete &amp; Masonry Primer<sup>2</sup> 2 cts. SuperPaint Exterior Latex</p> <p><b>Plywood</b> 1 ct. Exterior Latex Wood Primer 2 cts. SuperPaint Exterior Latex</p> <p><b>Wood (Cedar, Redwood)<sup>3</sup></b> 1 ct. Exterior Oil-Based Wood Primer<sup>2</sup> 2 cts. SuperPaint Exterior Latex</p> <p><sup>1</sup> On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher. <sup>2</sup> Not for use at temperatures under 50°F. See specific primer label for that product's application conditions. <sup>3</sup> Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of Exterior Oil-Based Wood Primer.</p> <p>Other primers may be appropriate. Standard latex primers cannot be used below 50°F. See specific primer label for that product's application conditions.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p><b>WARNING!</b> Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.</p> <p><b>Aluminum and Galvanized Steel</b> Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.</p> <p><b>Caulking</b> Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.</p> <p><b>Cement Composition Siding/Panels</b> Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 9, prime with Loxon Concrete &amp; Masonry Primer.</p>
Base	oz/gal	Strength															
Extra White	0-6	SherColor															
Deep Base	4-12	SherColor															
Ultradeep Base	10-12	SherColor															
Light Yellow	2-12	SherColor															



**SHERWIN  
WILLIAMS.**

# SUPERPAINT<sup>®</sup>

## Exterior Latex Flat

A80W00116 Super White  
A80W01151 Extra White  
A80W00153 Deep Base  
A80T01154 Ultradeep Base  
A80Y00156 Light Yellow

### SURFACE PREPARATION

#### **Masonry, Concrete, Cement, Block**

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.

#### **Steel**

Rust and mill scale must be removed using sandpaper, wire brush, or other abrading method. Bare steel must be primed the same day as cleaned.

#### **Stucco**

Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

#### **\*Vinyl or other PVC Building Products**

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, prime with appropriate white primer. Do not paint vinyl with any color darker than the original color or having a Light Reflective Value (LRV) of less than 56 unless VinylSafe<sup>®</sup> Colors are used. If VinylSafe colors are not used the vinyl may warp. Follow all painting guidelines of the vinyl manufacturer when painting. Only paint properly installed vinyl siding. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.

#### **Wood, Plywood, Composition Board**

Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All new and patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.

### SURFACE PREPARATION

#### **Mildew**

Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

### APPLICATION

When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the **air, surface, and material temperature** are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours.

Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.

No reduction necessary.

#### **Brush**

Use a nylon/polyester brush.

#### **Roller**

Use a 3/8" - 3/4" nap synthetic cover.

#### **Spray—Airless**

Pressure ..... 2000 psi

Tip ..... .015"-.019"

### CAUTIONS

For exterior use only.  
Protect from freezing.  
Non-photochemically reactive.  
Not for use on floors.

Before using, carefully read **CAUTIONS** on label.

HOTW 03/08/2018 A80W01151 33 38

KOR, FRC, Viet

### CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit [www.paintdocs.com](http://www.paintdocs.com) to obtain the most current version of the PDS and/or an SDS.



**SHERWIN  
WILLIAMS.**



# SUPERPAINT<sup>®</sup>

## Exterior Latex Satin

- A89W00116 Super White
- A89W01151 Extra White
- A89W00153 Deep Base
- A89T00154 Ultradeep Base
- A89Y00156 Light Yellow

As of 03/08/2018, Complies with:			
OTC	Yes	LEED <sup>®</sup> 09 NC CI	N/A
OTC Phase II	Yes	LEED <sup>®</sup> 09 CS	N/A
SCAQMD	Yes	LEED <sup>®</sup> v4 Emissions	N/A
CARB	Yes	LEED <sup>®</sup> v4 VOC	Yes
CARB SCM2007	Yes		
Canada	Yes	MPI	Yes

### CHARACTERISTICS

**SuperPaint Exterior Latex Satin**, with improved resistance to early dirt pick up, provides outstanding performance on properly prepared aluminum and vinyl siding, wood, hardboard, masonry, cement, brick, block, stucco, and metal down to a surface and air temperature of 35°F.

**VinylSafe™** paint colors allow you the freedom to choose from 100 color options, including a limited selection of darker colors formulated to resist warping or buckling when applied to a sound, stable vinyl substrate.

**Color:** Most colors  
To optimize hide and color development, always use the recommended P-Shadow primer

**Coverage:** 350 - 400 sq ft/gal  
@ 4 mils wet; 1.5 mils dry

**Drying Time, @ 50% RH:**  
@ 35-45°F @ 45°F +  
Touch: 2 hour 2 hours  
Recoat: 24-48 hours 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

**Finish:** 10-20 units @ 60°

**Tinting with CCE:**

Base	oz/gal	Strength
Extra White	0-6	SherColor
Deep Base	4-12	SherColor
Ultradeep Base	10-12	SherColor
Light Yellow	2-12	SherColor

**Extra White A89W01151**  
(may vary by base)

**VOC (less exempt solvents):**  
<50 g/L; <0.42 lb/gal  
As per 40 CFR 59.406 and SOR/2009-264, s.12

**Volume Solids:** 38 ± 2%  
**Weight Solids:** 49 ± 2%  
**Weight per Gallon:** 10.19 lb  
**Flash Point:** N/A  
**Vehicle Type:** 100% Acrylic  
**WVP Perms (US)** 26.14  
grains/(hr ft<sup>2</sup> in Hg)

**Mildew Resistant**

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

### SPECIFICATIONS

SuperPaint Exterior Latex Satin can be self-priming when used directly over existing coatings, or bare drywall, plaster and masonry (with a cured pH of less than 9). The first coat acts like a coat of primer and the second coat provides the final appearance and performance. Please note that some specific surfaces require specialized treatment.

**Aluminum & Aluminum Siding<sup>1</sup>, Galvanized Steel<sup>1</sup>, Vinyl Siding**

2 cts. SuperPaint Exterior Latex  
**Concrete Block, CMU, Split face Block**  
1 ct. Loxon Block Surfacer  
2 cts. SuperPaint Exterior Latex  
**Brick**

1 ct. Loxon Conditioner<sup>2</sup>  
2 cts. SuperPaint Exterior Latex  
**Cement Composition Siding/Panels**  
1 ct. Loxon Concrete & Masonry Primer<sup>2</sup>  
or Loxon Conditioner<sup>2</sup>  
2 cts. SuperPaint Exterior Latex

**Stucco, Cement, Concrete**

1 ct. Loxon Concrete & Masonry Primer<sup>2</sup>  
2 cts. SuperPaint Exterior Latex

**Plywood**

1 ct. Exterior Latex Wood Primer  
2 cts. SuperPaint Exterior Latex  
**Wood (Cedar, Redwood)<sup>3</sup>**  
1 ct. Exterior Oil-Based Wood Primer<sup>2</sup>  
2 cts. SuperPaint Exterior Latex

<sup>1</sup> On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.

<sup>2</sup> Not for use at temperatures under 50°F. See specific primer label for that product's application conditions.

<sup>3</sup> Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of Exterior Oil-Based Wood Primer.

Other primers may be appropriate. Standard latex primers cannot be used below 50°F. See specific primer label for that product's application conditions.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

### SURFACE PREPARATION

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

**Aluminum and Galvanized Steel**

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.

**Caulking**

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

**Cement Composition Siding/Panels**

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 9, prime with Loxon Concrete & Masonry Primer.



# SUPERPAINT<sup>®</sup>

## Exterior Latex Satin

- A89W00116 Super White
- A89W01151 Extra White
- A89W00153 Deep Base
- A89T00154 Ultradeep Base
- A89Y00156 Light Yellow

<u>SURFACE PREPARATION</u>	<u>SURFACE PREPARATION</u>	<u>CAUTIONS</u>
<p><b>Masonry, Concrete, Cement, Block</b> All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete &amp; Masonry Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.</p> <p><b>Steel</b> Rust and mill scale must be removed using sandpaper, wire brush, or other abrading method. Bare steel must be primed the same day as cleaned.</p> <p><b>Stucco</b> Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete &amp; Masonry Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.</p> <p><b>*Vinyl or other PVC Building Products</b> Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, prime with appropriate white primer. Do not paint vinyl with any color darker than the original color or having a Light Reflective Value (LRV) of less than 56 unless VinylSafe<sup>®</sup> Colors are used. If VinylSafe colors are not used the vinyl may warp. Follow all painting guidelines of the vinyl manufacturer when painting. Only paint properly installed vinyl siding. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.</p> <p><b>Wood, Plywood, Composition Board</b> Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All new and patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.</p>	<p><b>Mildew</b> Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised. Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p style="text-align: center;"><b><u>APPLICATION</u></b></p> <p>When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the <b>air, surface, and material temperature</b> are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours. No reduction necessary.</p> <p><b>Brush</b> Use a nylon/polyester brush.</p> <p><b>Roller</b> Use a 3/8" - 3/4" nap synthetic cover.</p> <p><b>Spray—Airless</b> Pressure ..... 2000 psi Tip ..... .015"-.019"</p>	<p><b><u>CAUTIONS</u></b></p> <p>For exterior use only. Protect from freezing. Non-photochemically reactive. Not for use on floors.</p> <p>Before using, carefully read <b>CAUTIONS</b> on label.</p> <p>HOTW 03/08/2018 A89W01151 36 39 Viet, KOR</p> <p style="text-align: center;"><b><u>CLEANUP INFORMATION</u></b></p> <p>Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit <a href="http://www.paintdocs.com">www.paintdocs.com</a> to obtain the most current version of the PDS and/or an SDS.</p>



**SHERWIN  
WILLIAMS.**



# SUPERPAINT<sup>®</sup>

## Exterior Latex Gloss

- A84W00116 Super White
- A84W01151 Extra White
- A84W00153 Deep Base
- A84T00154 Ultradeep Base

As of 03/08/2018, Complies with:

OTC	Yes	LEED <sup>®</sup> 09 NC CI	N/A
OTC Phase II	Yes	LEED <sup>®</sup> 09 CS	N/A
SCAQMD	Yes	LEED <sup>®</sup> v4 Emissions	N/A
CARB	Yes	LEED <sup>®</sup> v4 VOC	Yes
CARB SCM2007	Yes		
Canada	Yes	MPI	Yes

### CHARACTERISTICS

**SuperPaint Exterior Latex Gloss**, with improved resistance to early dirt pick up, provides outstanding performance on properly prepared aluminum and vinyl siding, wood, hardboard, masonry, cement, brick, block, stucco, and metal down to a surface and air temperature of 35°F.

**VinylSafe<sup>™</sup>** paint colors allow you the freedom to choose from 100 color options, including a limited selection of darker colors formulated to resist warping or buckling when applied to a sound, stable vinyl substrate.

**Color:** Most colors  
To optimize hide and color development, always use the recommended P-Shade primer

**Coverage:** 350 - 400 sq ft/gal  
@ 4 mils wet; 1.5 mils dry

**Drying Time, @ 50% RH:**  
@ 35-45°F @ 45°F+  
Touch: 2 hour 2 hours  
Recoat: 24-48 hours 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

**Finish:** 35-45 units @ 60°

**Tinting with CCE:**

Base	oz/gal	Strength
Extra White	0-6	SherColor
Deep Base	4-12	SherColor
Ultradeep Base	10-12	SherColor

**Extra White A84W01151**  
(may vary by base)

**VOC (less exempt solvents):**  
<50 g/L; <0.42 lb/gal  
As per 40 CFR 59.406 and SOR/2009-264, s.12

**Volume Solids:** 37 ± 2%

**Weight Solids:** 47 ± 2%

**Weight per Gallon:** 9.78 lb

**Flash Point:** N/A

**Vehicle Type:** 100% Acrylic

**WVP Perms (US)** 18.73  
grains/(hr ft<sup>2</sup> in Hg)

#### **Mildew Resistant**

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

### SPECIFICATIONS

SuperPaint Exterior Latex Gloss can be self-priming when used directly over existing coatings, or bare drywall, plaster and masonry (with a cured pH of less than 9). The first coat acts like a coat of primer and the second coat provides the final appearance and performance. Please note that some specific surfaces require specialized treatment.

#### **Aluminum & Aluminum Siding<sup>1</sup>, Galvanized Steel<sup>1</sup>, Vinyl Siding**

2 cts. SuperPaint Exterior Latex

#### **Concrete Block, CMU, Split Face Block**

1 ct. Loxon Block Surfacer

2 cts. SuperPaint Exterior Latex

#### **Brick**

1 ct. Loxon Conditioner<sup>2</sup>

2 cts. SuperPaint Exterior Latex

#### **Cement Composition Siding/Panels**

1 ct. Loxon Concrete & Masonry Primer<sup>2</sup>

or Loxon Conditioner<sup>2</sup>

2 cts. SuperPaint Exterior Latex

#### **Stucco, Cement, Concrete**

1 ct. Loxon Concrete & Masonry Primer<sup>2</sup>

2 cts. SuperPaint Exterior Latex

#### **Plywood**

1 ct. Exterior Latex Wood Primer

2 cts. SuperPaint Exterior Latex

#### **Wood (Cedar, Redwood)<sup>3</sup>**

1 ct. Exterior Oil-Based Wood Primer<sup>2</sup>

2 cts. SuperPaint Exterior Latex

<sup>1</sup> On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.

<sup>2</sup> Not for use at temperatures under 50°F. See specific primer label for that product's application conditions.

<sup>3</sup> Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of Exterior Oil-Based Wood Primer.

Other primers may be appropriate. Standard latex primers cannot be used below 50°F. See specific primer label for that product's application conditions.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

### SURFACE PREPARATION

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

#### **Aluminum and Galvanized Steel**

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.

#### **Caulking**

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

#### **Cement Composition Siding/Panels**

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 9, prime with Loxon Concrete & Masonry Primer.





**SHERWIN  
WILLIAMS.**

# SUPERPAINT<sup>®</sup>

## Exterior Latex Gloss

A84W00116 Super White  
A84W01151 Extra White  
A84W00153 Deep Base  
A84T00154 Ultradeep Base

### SURFACE PREPARATION

#### **Masonry, Concrete, Cement, Block**

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.

#### **Steel**

Rust and mill scale must be removed using sandpaper, wire brush, or other abrading method. Bare steel must be primed the same day as cleaned.

#### **Stucco**

Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

#### **\*Vinyl or other PVC Building Products**

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, prime with appropriate white primer. Do not paint vinyl with any color darker than the original color or having a Light Reflective Value (LRV) of less than 56 unless VinylSafe<sup>®</sup> Colors are used. If VinylSafe colors are not used the vinyl may warp. Follow all painting guidelines of the vinyl manufacturer when painting. Only paint properly installed vinyl siding. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.

#### **Wood, Plywood, Composition Board**

Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All new and patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.

### SURFACE PREPARATION

#### **Mildew**

Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

### APPLICATION

When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the **air, surface, and material temperature** are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours.

Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.

No reduction necessary.

#### **Brush**

Use a nylon/polyester brush.

#### **Roller**

Use a 3/8" - 3/4" nap synthetic cover.

#### **Spray—Airless**

Pressure..... 2000 psi

Tip ..... .015"-.019"

### CAUTIONS

For exterior use only.  
Protect from freezing.  
Non-photochemically reactive.  
Not for use on floors.

Before using, carefully read **CAUTIONS** on label.

HOTW 03/08/2018 A84W01151 33 35

Viet, KOR

### CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit [www.paintdocs.com](http://www.paintdocs.com) to obtain the most current version of the PDS and/or an SDS.



**SHERWIN  
WILLIAMS.**

101.02

**SUPERPAINT®**  
Interior Latex  
Flat

A86W00150 Hi-Refl White  
A86W00151 Extra White  
A86W00153 Deep Base  
A86T01154 Ultradeep Base

As of 01/14/2016, Complies with:			
OTC	Yes	LEED® 09 CI	Yes
SCAQMD	Yes	LEED® 09 NC	Yes
CARB	Yes	LEED® 09 CS	Yes
CARB SCM 2007	Yes	LEED® 09 H	Yes
MPI	Yes	NGBS	Yes

**CHARACTERISTICS**

SuperPaint Interior Latex Flat is for use on previously painted, bare or primed wallboard and wood, and primed plaster, masonry and metal. SuperPaint paint and primer in one provides fast & easy application, while offering excellent hide and durability.

**Color:** Most colors  
To optimize hide and color development, always use the recommended P-Shade primer

**Coverage:** 350 - 400 sq ft/gal  
@ 4 mils wet; 1.7 mils dry

**Drying Time, @ 77°F, 50% RH:**  
Touch: 1 hour  
Recoat: 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

**Flash Point:** N/A

**Finish:** 0-5 units @ 85°

**Tinting with CCE:**

Base	oz/gal	Strength
Hi Refl White	0-5	Sher-Color
Extra White	0-6	Sher-Color
Deep Base	4-12	Sher-Color
Ultradeep Base	4-12	Sher-Color
<b>Vehicle Type:</b>		Vinyl Acrylic

**Extra White A86W00151**

**VOC (less exempt solvents):**  
<50 g/L; 0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s.12

**Volume Solids:** 43 ± 2%

**Weight Solids:** 61 ± 2%

**Weight per Gallon:** 12.05 lb

**SPECIFICATIONS**

SuperPaint Interior Latex can be used **directly over existing coatings, or bare drywall, plaster (cured with a pH of less than 9), masonry (cured with a pH of less than 9) and non-bleeding wood.**

**Drywall**

Self-prime using 2 cts. of SuperPaint Interior Latex

or  
1 ct. Premium Wall & Wood Primer  
2 cts. SuperPaint Interior Latex

**Masonry / Block**

(can be filled to provide a smooth surface or primed if it is a high pH substrate)

1 ct. Loxon Block Surfacer  
or  
1 ct. Loxon Concrete & Masonry Primer  
2 cts. SuperPaint Interior Latex

**Plaster**

Self-prime using 2 cts. of SuperPaint Interior Latex

or  
1 ct. Premium Wall & Wood Primer  
2 cts. SuperPaint Interior Latex

**Wood**

Self-prime using 2 cts. of SuperPaint Interior Latex

or  
1 ct. Premium Wall & Wood Primer  
2 cts. SuperPaint Interior Latex  
If the wood has bleeding (such as tannin or knot-holes), prime with Multi-Surface Primer.

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

**SURFACE PREPARATION**

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

**Drywall**

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

**Masonry, Concrete, Cement, Block**

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.



**SHERWIN  
WILLIAMS.**

# SUPERPAINT®

## Interior Latex Flat

A86W00150 Hi-Refl White  
A86W00151 Extra White  
A86W00153 Deep Base  
A86T01154 Ultradeep Base

<u>SURFACE PREPARATION</u>	<u>APPLICATION</u>	<u>CAUTIONS</u>
<p><b>Plaster</b> Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p><b>Wood</b> Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p><b>Mildew</b> Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised. Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p><b>Caulking</b> Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.</p>	<p>Apply at temperatures above 50°F. No reduction needed.</p> <p><b>Brush</b> Use a nylon/polyester brush.</p> <p><b>Roller</b> Use a 3/8" - 3/4" nap synthetic cover.</p> <p><b>Spray—Airless</b> Pressure..... 2000 psi Tip..... .017"-.021"</p> <p><u><b>CLEANUP INFORMATION</b></u> Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.</p>	<p>For interior use only. Protect from freezing. Non-photochemically reactive.</p> <p>Contains <b>CRYSTALLINE SILICA</b>. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (<b>NIOSH</b> approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (<b>NIOSH</b> approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. <b>FIRST AID:</b> In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. <b>DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.</b> Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. <b>WARNING:</b> This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. <b>DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN</b></p> <p>HOTW 01/14/2016 A86W00151 15 42</p> <p>KOR, FRC</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit <a href="http://www.paintdocs.com">www.paintdocs.com</a> to obtain the most current version of the PDS and/or an SDS.</p>